

ELECTRICAL ACCESSORIES

Item	Model No	Description
	Weton U-Type Photoelectric Switch Model No.: E3S-GS3B4 (PNP Output) E3S-GS3E4 (NPN Output)	Electrical Specification : Supply Voltage : 12-24Vdc, Current consumption $\leq 40\text{mA}$ Output Type : PNP Open collector output type NPN Voltage output type Environmental Specifications : Operating temperature : 0 to +80°C Storage temperature : -20 to +80 °C
	Wire wound type DBR	Electrical Specification : Wire wound type DBR for Elevator Drives Rating from 3.7KW to 22KW
	Aluminum type DBR	Electrical Specification : Aluminum type DBR for Elevator Drives Rating from 3.7KW to 22KW
	Limit Switches (ESBEE Make)	No & NC type for Elevator application
	Door PM Motor (Monarch Make)	Available : • 2.7 Nm (Suitable for 700 mm to 800 mm Door Opening) • 5.5 Nm (Suitable for 900 mm to 1100 mm Door Opening) • 7 NM (Suitable for 1200 mm to 2200 mm Door Opening)
	Intercom (BST Make)	Available : • Two way System • Three way System • Five way System • Operating Voltage 12V & 24V DC
	Elevator Access Control System (Biometric, RFID & Passwords Based)	Available : • Finger Print • RFID • Password
	Sin Cos Encoder (Suitable for Gearless motor) Weton make Fenac make	Electrical Specification : • Rotating speed $\leq 2000\text{ rpm}$ • Supply Voltage : 5Vdc ($\pm 5\%$) • Resolution : 2,048PPR
	Rotary Incremental Encoder (Suitable for Geared motor) Weton make Fenac make	Electrical Specification : • Hole Diameter : 30~45 mm, • Voltage 10~30V Open Collector • 10~30V, 15V Push-Pull • Resolution : 1024 and 4096 PPR